

🔥🔥 COMPACT RULES 2024!!

Adult & youth

0.) Any engine and trans maybe used in any car 4cyl or 6 cyl only may only weld lower engine mounts to frame or subframe. No cradles or protectors of any kind.

1.) All car prep is the same as other classes. All debris, glass, and any flammable must be removed.

2.) The wheelbase is 110" max!

3.) No suv, or mini vans. No v8s or 4x4

4.) Bumpers may be interchangeable. Any factory oem car bumper may be used excluding chrysler pointy ... **NO POINTY**

BUMPERS....NO HOMEADE BUMPERS..... may seam weld

bumpers may stuff bumper between skin and backing. Bumpers must be trimmed so they arent wider than the outside of the tires.

CALL IF YOU HAVE QUESTIONS. No bumper brackets allowed

unless they are the factory brackets and shocks for that car. bumper may be welded to the shock. May collapse the shock... do not weld

the the shock or the brackets to the frame... You may hard nose if you choose. May only weld bumper to frame with one 1/2" pass all

the way around. If doing so factory shocks and brackets must be removed. No other material may be used at all!

5.) May change 2 front core support bolts to 3/4 allthread they can go through top of frame but must not extend under frame. No body

bolts may be changed. Do not even touch them period! If one is rotted out or missing, you may use a single loop of 9 wire to tire it

back. If body bolts or cradle bolts have been changed, you will not be permitted to run!

6.) No aftermarket suspension or steering allowed... no reinforcing steering or suspension components period! All parts must be stocked.

7.) You may run aftermarket pedal setup... must not re inforce car in any way! After market steering allowed also from steering wheel to steering box or rack may not re inforce car in any way.

8.) A 4pt. Cage will be allowed. May have 1 down bar perside of the car in the middle of the front doors. This is for safety period! Door bars or and seat bar Cannot go any further back than 6 inches behind front door seam!! Halo is allowed. Must be vertical and go to topside of cage..cannot go to the floor. Gas tank protector is allowed. Must be positioned in center of seat bar. Can only be 24" wide. Must be 6" from any sheetmetal, this includes doors, wheel wells, floor, and package tray. I know cars are different, but you choose the cars not us! No cage material may exceed 4" material.

9.) Hood may be left on stock hinges. Must have a 12x12 hole in hood for safety in case of fire. (6) 3/4" pieces of all thread total. (2) All thread can run through the core support mounts extending through the hood as a hood bolt. Factory rubber bushing must be in place. No welding all thread in place at core support. Allthread must not extend past bottom of frame . Hood plates must be max 4x4x1/4 and may use 3 3/4 nuts and washers per allthread sheet metal to sheet metal only. You may also weld allthread to inner fender sheetmetal or firewall sheetmetal if you choose to do this only 1 plate washer and nut may be used to secure hood per allthread. If you dont use allthread you may chain or nine wire hoods down after inspection in 6 places. You are allowed 20 3/8 bolts with 40 washers and 20 nuts to bolt around holes cut in hood for headers or safety holes in case of fire.

10.) The truck deck may be folded and tucked and welded 5on 5 off with 3" wide by 1/8" thick strap or may use 6 3/4 allthread like hood rules to secure trunk lid or tailgate hatch etc sheet metal to sheet metal onlyQuarters may be creased. if wheel wells are cut for clearance may use 8 3/8 bolts with washers and nut to bolt sheetmetal back together

11.) The car must have a window bar infront of driver.

12.) Fuel tanks must be removed, and fuel cell or steel boat tank fastened in backseat area!!! You may run the factory metal tank as long as it is factory location under car and is in front of rear end... no plastic tanks!!

14.) Drivers' door may be welded solid with 3" wide by 1/8" thick strap. All other doors may be welded 5 on 5 off with 3" wide by 1/8" thick strap. Pillars may be duct taped... if you choose to chain or 9 wire doors that is fine may have 3 pieces per door and may duct tape pillars as well...

15.) No frame welding whatsoever!!! If only exception is on pre-ran cars you may have 2 4x6x1/4" plate per rail... must be on the rail not cradle... may be located on any side of the exterior of the frame... if it covers a frame hole have a 1/2" hole pre-cut or you will cut one... any questions call!!!!

16.) Solid forklift tires will be allowed on the back of fwd cars. All other wheels may only have a small center... skidders are allowed, no foam filled tires or solid tires allowed on the drive's axels period!

17.) Rwd cars all leaf springs must remain factory. No added leafs period!

18.) All cars are permitted in 4 places of 9 wire. 2 loops making 4 strands... maybe ran however you'd like.

19.) All cars must have a 3/8" inspection hole 3" behind the front bumper, in the middle of the frame, on the wheel side of the frame for tech. Anything found inside the frame you will be loaded.